



Attestation of Conformity

No. N8A 130131 0001 Rev. 01

Holder of Attestation: **Sunrise energy Co., Ltd.**
No.20 Tongzi River West Road, Zhonglou Development Zone
213016 Changzhou, Jiangsu
PEOPLE'S REPUBLIC OF CHINA

Product: **Crystalline Silicon Terrestrial Photovoltaic (PV) Modules**
Mono-Crystalline Silicon Photovoltaic Module

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 704062505101-01

Date, 2026-06-09

(Zhulin Zhang)

Page 1 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Attestation of Conformity

No. N8A 130131 0001 Rev. 01

Model(s):

SR-66MAXxxxNHD, xxx = 670 to 730 in steps of 5;
SR-60MAXxxxNHD, xxx = 610 to 665 in steps of 5;
SR-66MxxxNHLProDR, xxx = 585 to 640 in steps of 5;
SR-60MxxxNHLProDR, xxx = 535 to 580 in steps of 5;
SR-54MxxxNHLProDR, xxx = 480 to 525 in steps of 5;
SR-48MxxxNHLProDR, xxx = 425 to 465 in steps of 5;
SR-72MxxxNHLProDM, xxx = 605 to 640 in steps of 5;
SR-66MxxxNHLProDM, xxx = 555 to 585 in steps of 5;
SR-60MxxxNHLProDM, xxx = 505 to 530 in steps of 5;
SR-54MxxxNHLProDM, xxx = 455 to 480 in steps of 5;
SR-72MxxxNHLProDII, xxx = 585 to 615 in steps of 5;
SR-66MxxxNHLProDII, xxx = 535 to 560 in steps of 5;
SR-54MxxxNHLProDII, xxx = 440 to 460 in steps of 5;
SR-72MxxxNHLProDI, xxx = 570 to 615 in steps of 5;
SR-66MxxxNHLProDI, xxx = 520 to 565 in steps of 5;
SR-60MxxxNHLProDI, xxx = 470 to 515 in steps of 5;
SR-54MxxxNHLProDI, xxx = 425 to 460 in steps of 5;
SR-78MxxxNHLProD, xxx = 605 to 650 in steps of 5;
SR-72MxxxNHLProD, xxx = 555 to 600 in steps of 5;
SR-72MxxxNHLProDA, xxx = 555 to 600 in steps of 5;
SR-66MxxxNHLProD, xxx = 510 to 550 in steps of 5;
SR-60MxxxNHLProD, xxx = 465 to 500 in steps of 5;
SR-54MxxxNHLProD, xxx = 415 to 450 in steps of 5;
SR-54MxxxNHLProDA, xxx = 415 to 450 in steps of 5;
SR-48MxxxNHLProD, xxx = 370 to 400 in steps of 5;
xxx is standing for rated output power at STC

Parameters:

Construction:	Framed, with Junction box, Cable and Connectors.
Safety Class:	Class II
Maximum System Voltage:	1500 V DC
Fire Safety Class:	Class C according to UL790

Tested according to:

EN IEC 61730-1:2018
EN IEC 61730-1:2018/AC:2018-06
EN IEC 61730-2:2018
EN IEC 61730-2:2018/AC:2018-06

Page 2 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.